

PROFESS

V9080



Model	V9080
Enclosure外型	3U 16-BAY
Appearance外觀	3U19 "Rackmount
Drive Max硬碟數量	16 x Hot-swappable+2 x 2.5 "(OS HDD)
CPU處理器	Intel® 10th Gen Core i3 / i5 / i7 / i9 series
System memory 記憶體系統	4 x DIMM slots / Unbuffered non-ECC UDIMM, DDR4-2933MHz / Up to 128GB
PCI-Express Slot · PCI-Express 插槽	1 PCI-E 3.0 x16 (in x16 slot) 1 PCI-E 3.0 x8, 2 PCI-E 3.0 x4
M.2模組	M.2 Interface: 1 PCI-E 3.0 x4, RAID 0 & 1 Form Factor: 2242/2280 Key: M-Key
Default Port 網路介面	2 RJ45 Gigabit Ethernet LAN ports
Management Software 管理軟體	SuperDoctor® 5, SUM, AMT, vPro, Watchdog
On-Board Devices機載設備	Chipset : Intel® Q470E SATA : Intel® Q470 controller for 6 RAID 0,1,5,10 Graphics : Intel® HD Graphics
RAID Controller Card 磁碟陣列控制卡	12 Gb dual core ROC-based SAS solution / up to 128 SAS or SATA devices Cache memory options: – 1 GB 1866 MHz DDR3 SDRAM – 2 GB 1866 MHz DDR3 SDRAM
Supported RAID支援磁碟陣列	RAID levels 0, 1, 5, 6, 10, 50, and 60
Supported Disk支援硬碟	2.5 " SATA SSD / 2.5" SAS SSD / 2.5" 10K RPM SAS HDD / 2.5" 15K RPM SAS HDD 3.5" 7200 RPM SATA HDD/ 3.5" 7200 RPM NL SAS HDD
SAS Expansion Ports擴充介面	1 or 2port 12Gb/s SAS expansion port (Optional)
External Interface 外接介面	1 VGA port(s), 1 DP (DisplayPort) port(s), 1 HDMI port(s), 1 DVI - D port(s) 6 USB 3.1 Gen2 port · 6 USB 2.0 1 TPM Header & Chip both
System HDD系統硬碟	Support 2.5" HDD or SSD 2 x 2.5" HDD or SSD Hot-swappable (Optional)
FAN model散熱模組	3x80x38mm PWM & low-power consumption hot swap fans
PSU model 電源模組	800W 1+1 redundant PSU PMBus 1.2 80+ Platinum
Size (W x D x H)尺寸	430 x 680 x 133mm
Safety / EMI安全認證	CE / FCC / BSMI