

3Gen® 4U 60bay SAS / SATA HDD JBOD

Hot-swappable and Modularized 6G JBOD Series

Features

- ✓ 60 x 3.5" top-loading hot-swappable HDD supported
- ✓ 1890W 3+1 or 1350W 2+2 redundant 80+ power supply
- ✓ Hot-swappable cooling fan, 4PIN support PWM
- ✓ 1 x LSI 28 ports + 2 x LSI 36 ports 6G expander
- ✓ Zoning support (1 x 60 HDDs, 2 x 30 HDDs, 4 x 15 HDDs)
- ✓ Self-configuration to host and client
- ✓ Dual expanders



SPECIFICATIONS

General :

- ✓ Number of Expander : Single / Dual
- ✓ Expander Chip : 1 x LSISA 2 x 28 + 2 x LSISA 2 x 36 per expander
- ✓ Expansion Interface : 4 x mini SAS 8088 connector per expander

Drives Supported :

- ✓ Drive Interface : 3.0 / 6.0 Gb dual ported SAS , 3.0 / 6.0 Gb single ported SATA
- ✓ Drive RPM : Up to 15,000
- ✓ Form Factor : 3.5" , 1" height

Administration / Management :

- ✓ Admin / Firmware Upgrade : In-band & Serial port
- ✓ LED Indicators : Yes

Hot-swap and Redundancy :

- ✓ Disk Drive : Hot-swap 60-bay
- ✓ Cooling : 2 x 8038 hot-swap fans and 2 x 6038 hot-swap fans
- ✓ Power Supply : 1890W 3 + 1 or 1350W 2 + 2 hot-swap redundant 80+ (Silver)
- ✓ Expander : Dual hot-swap expanders (not available for single expander version)

Electrical and Environmental :

- ✓ Universal A/C Input : 100~240 V AC full range
- ✓ Operating Environment : Temperature 0°C to 35°C / Relative humidity 20% to 80%
- ✓ Non-operating Environment : Temperature -20°C to 60°C / Relative humidity 10% to 90%

Physical Specification:

- ✓ Dimensions (W x D x H) : 480 x 885.3 x 175 mm
- ✓ Gross Weight (w /PSU and Rail) : 75.4 kgs / 166 lbs
- ✓ Mounting Option : 28" tool-less rail (optional)



60 x 3.5" top-loading hot-swappable HDD supported

