

PROFESS

V9080Pro



Model	V9080Pro
Enclosure外型	3U 16-BAY
Appearance外觀	3U19 "Rackmount
Drive Max硬碟數量	16 x x Hot-swappable+2 x 2.5 "(OS HDD)
CPU處理器	Intel® Xeon Scalable processor product family / Model: PRODP1 (Support 2 x CPU)
System memory 記憶體系統	16 x DIMM slots / DDR4 ECC UDIMM 2400 / 2666 / 2933 MHz / 16GB DDR4 ECC RDIMM STD (MAX 4TB)
PCI-Express Slot · PCI-Express 插槽	4 PCI-E 3.0 x16 / 2 PCI-E 3.0 x8
M.2模組	M.2 Interface: PCI-E 3.0 x4 Form Factor: 2260, 2280, 22110 Key: M-Key
Default Port 網路介面	2 RJ45 Gigabit Ethernet LAN ports / Dual LAN with 1GbE LAN with Intel® X722
ManagementSoftware 管理軟體	Intel® Node Manager / IPMI2.0 / KVM with dedicated LAN / SPM / SSM / SUM / SuperDoctor® 5 / Watchdog
On-Board Devices機載設備	Chipset : Intel® C621 SATA : Intel® C621 controller for 14 SATA3 (6 Gbps) ports; RAID 0,1,5,10 Graphics : ASPEED AST2500 BMC
RAID Controller Card 磁碟陣列控制卡	12 Gb dual core ROC-based SAS solution / up to 128 SAS or SATA devices Cache memory options: – 1 GB 1866 MHz DDR3 SDRAM – 2 GB 1866 MHz DDR3 SDRAM
Supported RAID支援磁碟陣列	RAID levels 0, 1, 5, 6, 10, 50, and 60
Supported Disk支援硬碟	2.5" SATA / SAS SSD / 2.5" 10K RPM SAS HDD/ 2.5" 15K RPM SAS HDD 3.5" 7200 RPM SATA HDD/ 3.5" 7200 RPM NL SAS HDD
SAS Expansion Ports擴充介面	1 or 2 x 12Gb/s SAS expansion port (Optional)
External Interface 外接介面	4 USB 2.0 ports · 5 USB 3.2 Gen1 ports / 1 VGA port / 2 COM Ports / 1 TPM Header
System HDD系統硬碟	Support 2.5" HDD or SSD / 2 x 2.5" HDD or SSD Hot-swappable (Optional)
FAN model散熱模組	3 x 80 x 38mm PWM & low-power consumption hot swap fans
PSU model 電源模組	800W 1+1 redundant PSU PMBus 1.2 80+Platinum
Size (W x D x H)尺寸	430 x 680 x 133mm
Safety / EMI安全認證	CE / FCC / BSMI